




## BL6001 LED 4W

### Applications

Cylinder downlights ceiling mounted or pendant mounted to provide under-canopy general lighting. Choices of housing colour allow luminaire to blend perfectly with ceiling/canopy finish.

### Dimensions



### Specifications

<b>Housing</b>	Extruded aluminum
<b>Cover and Side Arm</b>	Die-cast aluminum
<b>Gasket</b>	Silicone rubber
<b>Cover Lens</b>	Tempered Glass
<b>LED Optic</b>	PMMA Lens
<b>Surface Finish</b>	AkzoNobel powder coating
<b>Driver Type</b>	Constant current
<b>Input Voltage</b>	120~277V/AC
<b>Ambient Temperature</b>	-20°C~45°C
<b>CCT</b>	3000K _ 4000K _ 6000K_R_G_B_RGB
<b>Beam Angle</b>	5°/15°/25°/45°/60°


<b>LED Lumens</b>	3000K - 375lm
	4W 4000K - 390lm
	6000K - 426lm

<b>Ingress Protection</b>	IP65
---------------------------	------

### Certifications



### Photometric Data



### Ordering Guide:

Example: BL6001 - C4 - 3 - 25 - 80 - RAL7012

1 Series	2 Power	3 CCT	4 Beam angle	5 Ra	6 Housing Colour	7 Accessories
BL6001	C4: LED 1WX3	3: 3000K 4: 4000K 6: 6000K R: Red G: Green B: Blue RGB: RGB	05: 5° 15: 15° 25: 25° 45: 45° 60: 60°	80: Ra80 90: Ra90	B: Black RAL9011 W: White RAL9016 G: Gray RAL7012 Z: Mineral bronze	M: Marine ambient corrosion resistance DMX: DMX Decoder P: Pendant mount 3' hanging cable

