



### BL6015 LED 11W

#### Applications

Round wall sconces, aimed either up or down, with multiple beam angle choices, to graze columns or to create light level contrast on wall façade. Choices of housing colour allow the luminaire to blend perfectly with exterior architectural colours under daylight.

#### Specifications


Housing	Extruded aluminum
Cover and Side Arm	Die-cast aluminum
Gasket	Silicone rubber
Cover Lens	Tempered Glass
LED Optic	PMMA Lens
Surface Finish	AkzoNobel powder coating
Driver Type	Constant current
Input Voltage	120~277V/AC_except 24V.DC for RGB
Ambient Temperature	-20°C~45°C
Ingress Protection	IP65

#### Certifications





RGB REQUIRES LISTED  
REMOTE DRIVER


#### Dimensions



#### Photometric Data



Downlight Only



Uplight Only

#### Ordering Guide:

Example: **BL6015D - C11- 3 - 25 - 80 - G - T**

1 Series	2 Power	3 CCT	4 Beam angle	5 Ra	6 Housing Colour	7 Accessories
BL6015D: Downlight BL6015U: Uplight	C11: LED 11W	3: 3000K 4: 4000K 6: 6000K R: Red G: Green B: Blue RGB: R.G.B	05: 5° 15: 15° 25: 25° 45: 45° 60: 60°	80: Ra80	B: Black RAL9011 W: White RAL9016 G: Gray RAL7012 Z: Mineral bronze S: Silver RAL9006	T: 20° tilt to wall M: Marine ambient corrosion resistance DMG: 0-10V Dimming MT: Mounting plate for standard junction box

