



### BL6120 LED 11W, 15W

#### Applications

Square wall sconces, aimed either up or down, with multiple beam angle choices, to graze columns or to create light level contrast on wall façade. Choices of housing colour allow the luminaire to blend perfectly with exterior architectural colours under daylight.



#### Specifications

|                      |                          |
|----------------------|--------------------------|
| Housing and Side Arm | Extruded aluminum        |
| Cover                | Die-cast aluminum        |
| Gasket               | Silicone rubber          |
| Cover Lens           | Tempered Glass           |
| LED Optic            | PMMA Lens                |
| Surface Finish       | AkzoNobel powder coating |
| Driver Type          | Constant current         |
| Input Voltage        | 120~277V/AC              |
| Ambient Temperature  | -20°C~45°C               |
| Ingress Protection   | IP65                     |


#### Certifications



#### Dimensions



Downlight Only



Uplight Only

#### Ordering Guide:

Example: **BL6120 - C11 - 3 - 15 - 80 - G**

| 1                                      | 2                            | 3                                | 4   | 5                    | 6   | 7   |
|--|------------------------------|----------------------------------|---|----------------------|---|---|
| Series                                 | Power                        | CCT                              | Beam angle  | Ra                   | Housing Colour  | Accessories   |
| BL6120D: Downlight<br>BL6120U: Uplight | C11: LED 11W<br>C15: LED 15W | 3: 3000K<br>4: 4000K<br>5: 5000K | 15: 15°<br>23: 23°<br>38: 38°<br>45: 45°<br>60: 60° | 80: Ra80<br>90: Ra90 | B: Black RAL9011<br>W: White RAL9016<br>G: Gray RAL7012<br>Z: Mineral bronze<br>S: Silver RAL9006 | M: Marine ambient corrosion resistance<br>T: 20° tilt to wall<br>MT: Mounting plate for standard junction box |

